



120.00 mm

BLAUPUNKT



Rear of Unit



PIN	DEFINITION A PART	PIN	DEFINITION B PART
1	NC	1	Rear R+
2	NC	2	Rear R-
3	NC	3	Front R+
4	ACC	4	Front R-
5	Auto Antenna*	5	Front L+
6	NC	6	Front L-
7	Perm. +12V	7	Rear L+
8	GND	8	Rear L-

DEFINITION C PART					
PIN	C1 PART	PIN	C2 PART	PIN	C3 PART
1	Video GND	7	Reverse	13	NC
2	NC	8	+12V Switched*	14	NC
3	NC	9	SWC 2	15	NC
4	Camera Video	10	Brake	16	NC
5	NC	11	SWC GND	17	NC
6	NC	12	SWC 1	18	NC
--	---	--	---	19	NC
--	---	--	---	20	NC

PIN	DEFINITION
1	Rear Video OUT 2
2-12	NC
13	Video GND
14-20	NC
21	Front L
22	Front R
23	Audio GND
24	Rear L
25	Rear R
26	NC
27	SLIB OUT
28	Audio GND
29	Rear L OUT
30	Rear R OUT
31	Rear Video OUT 1
32	AUX IN Video
33	Video GND
34	AUX Audio GND
35	AUX IN L
36	AUX IN R

Remarks: (*) Total max. 150 mA / Fuse: 15 Ampere
Voltage: 12V DC; Negative Ground

Warnings:

Warranty void if this unit is damaged due to misuse or unauthorized service attempting.

Before making any electrical connections disconnect the vehicle battery's negative terminal and carefully read the unit's Owner's Manual.

Connect each pair of speaker leads only to a single pair of speakers (or speaker system) that has an impedance of at least 4 ohms, as well as 50-watt power handling capability. Never allow the uninsulated part of any speaker leads to touch a metal part of the vehicle.

Connect speaker leads to input of external amplifiers ONLY if indicated in amplifier's manual, otherwise this unit's internal amplifier will be damaged.

This product was produced using lead free technology. Help keep the world clean! Dispose properly!



See other **BLAUPUNKT** products at www.blaupunkt.com

DEALER

DATE SOLD/INSTALLED

100.00 mm